

Explosion Proof Peristaltic Pump

Model No.: EXP600-1/YZ Series

Flow Rate: 4.2-2280mL/min



Product Features

JDiven by explosion-proof motor, the power is strong.

Stepless speed regulation, reversible inversion.

IP rate: IP55, Explosion-proof grade:ExdIIBT4 Gb

Suitable for inflammable and explosive industrial sites.

Pump Head



YZ1515x



YZ2515x

Drive	Speed(rpm)	Pump Head	Tube Size	Flow Rate (mL/min)
EXP600-1/YZ Series	600	YZ1515x	13#, 14#, 19#, 16#, 25#, 17#, 18#	4.2-2280
		YZ2515x	15#, 24#	102-1740

Technical Specifications

Speed range	Manual control: 180-600 rpm; Frequency converter control: 60-600rpm
Speed control	Manual stepless speed regulation/Inverter speed regulation
Voltage	3 phase 380V(standard)/3 phase 220V(optional)
Condition temperature	0-40°C
Relative humidity	<80%
Explosion-proof grade	ExdIIBT4 Gb, ExdIICT4
IP rate	IP55
Drive weight	30kg
Drive dimension(L xWxH)	424 x230x330(mm)

Dimension Drawing(Unit:mm)

