

Explosion Proof Peristaltic Pump

Model No.: EXP600-A-IV-1/DZ25-3L

Flow Rate: 126.6-3600mL/min



Product Features

JDiven by explosion-proof motor, the power is strong.

Stepless speed regulation, reversible inversion.

IP rate: IP55, Explosion-proof grade:ExdIIBT4 Gb

Suitable for inflammable and explosive industrial sites.

Pump Head



DZ25-3L(PPS)



DZ25-3L(Aluminum Alloy)

Drive	Speed(rpm)	Pump Head	Tube Size	Flow Rate (mL/min)
EXP600-A-IV-1/DZ25-3L	60-600	DZ25-3L	15#, 24#, 35#, 36#	126.6-3600

Technical Specifications

Speed range	Manual control: 180-600 rpm; Frequency converter control: 60-600rpm
Speed control	Manual stepless speed regulation/Inverter speed regulation
Voltage	3 phase 380V(standard)/3 phase 220V(optional)
Condition temperature	0-40°C
Relative humidity	<80%
Explosion-proof grade	ExdIIBT4 Gb,ExdIICT4
IP rate	IP55
Drive weight	30kg
Drive dimension(L xWxH)	424 x230x330(mm)

Dimension Drawing(Unit:mm)

