


Fast Load Pump Head



Aluminium Alloy



Model No.: DZ25-3L

Flow Rate :

0.211-3600mL/min

Product Features

Easy operation, change tube rapidly. The house material is PPS (polyphenylene sulfite). 304 stainless steel rollers.

DZ25 pump head use 2.4mm wall thickness tube, the flow rate range is 0.211-3600mL/min. This pump head is suitable for high viscous liquid which include granule and floc. It also suitable for high pressure request. New cartridge structure design, can use the special connector, connect low cost tubing outside the pump head to save cost; also can use flexible tube clamp, meet hygiene requirement.

Typical Application

- 1.This pump head is suitable for high viscous liquid which include granule and floc.
- 2.It is also suitable for high pressure request.

Technical Specifications

Pump Head	Housing Material	Tubing Clamp Material	Tubing		Flow Rate(mL/min) 0.1~600(rpm)	Weight(kg)
			Tubing Size	ID×Wall thickness		
DZ25-3L	PPS	PP	15#	4.8×2.4(mm)	0.211~1264	0.5
			24#	6.4×2.4(mm)	0.385~2310	
			35#	7.9×2.4(mm)	0.508~3050	
			36#	9.6×2.4(mm)	0.6~3600	

Tubing Installation



A. Lift both side levers, take off the upper block.



B. Put the tubing with cartridge or connector into pump housing.



C. Install the upper block, put down the levers to lock the block.

Dimension Drawing (Unit:mm)

